



**InfiLINK XG** is InfiNet's most recent addition to our wireless portfolio. It is a record-breaking and innovative Point-to-Point solution in the sub-7 GHz frequency band, boasting the best-in-breed spectral efficiency, higher-than-ever-before processing power and distance vs. performance ratio. Reaching a peak of 480 Mbps of net throughput in 40 MHz of spectrum, and more than 100 Mbps in only 10 MHz, it is the fastest Point-to-Point system available in the marketplace today.

Available with a wide range of integrated antennas, as well as a connectorized version for use with 3rd party external antennas, and coupled with improved transmit power and sensitivity, the XG family will fit perfectly into a large array of applications such as backhaul in the telecom market, education, oil and gas, smart cities, video surveillance and public safety. It was designed by InfiNet to meet the exact requirements of the most demanding customers, most complex projects and most challenging environments.

## APPLICATIONS

- ▶ HIGH CAPACITY SHORT-, MEDIUM- AND LONGHAULS FOR 3G/4G OPERATORS AND SERVICE PROVIDERS
- ▶ FULL-FLEDGED FIBRE/FSO/MILLIMETRE-WAVE REPLACEMENT, EXTENSION OR BACKUP
- ▶ LOS AND NLOS MACRO- AND SMALL-CELL BACKHAUL
- ▶ VIDEO SURVEILLANCE OVER MEDIUM AND LONG DISTANCES
- ▶ DISASTER RECOVERY
- ▶ BUILDING-TO-BUILDING CONNECTIVITY
- ▶ RURAL/SUBURBAN LAST MILE ACCESS

# INFILINK XG

## Top Facts Sheet



### HIGHEST SPECTRAL EFFICIENCY

Best-in-class 13 bps/Hz  
In excess of 100 Mbps net throughput even in only 10 MHz channel width  
Innovative radio technology for NLOS and reflected signal conditions

### SUPERIOR PERFORMANCE AND PROCESSING POWER

Unmatched 1 million packets-per-second processing power  
Full capacity at any packets sizes and for any type of traffic

### UNMATCHED CAPACITY

Net performance of 240 Mbps in 20 MHz and 480 Mbps in 40 MHz

### LONGEST REACH

Distances in excess of 30 km with integrated antennas, and more than 100 km with external high gain antennas  
High-power transmitter and high sensitivity even at highest modulations, ensuring maximal link budget  
Unprecedented system gain of 177 dB even with integrated antennas

### SEAMLESS INTEGRATION

Extended QoS support  
Two Gigabit Ethernet ports  
SFP optical port  
IEEE 1588  
Full-fledged L2 switching

### FLEXIBILITY

Available in connectorized configuration and with integrated 23 dBi and 28 dBi flat-panel dual-polarity antennas  
Easy-to-align and easy-to-install  
Fully configurable uplink/downlink ratio  
Very small footprint

### ULTRA-LOW LATENCY

Ultra-low consistent 0.5 ms latency at any distance  
Configurable frame size

### RELIABILITY & ROBUSTNESS

Ruggedized aluminium cast IP66 enclosure  
Extended temperature range of -40° to +60°C, with 100% humidity  
No link degradation even in harsh weather conditions  
Built-in surge protection

### IMPROVED NOISE IMMUNITY / INTERFERENCE AVOIDANCE

On-site synchronization for best spectrum utilization  
-40 dB adjacent channel separation



# INFILINK XG Technical Specifications

## PERFORMANCE

Throughput	Up to 480 Mbps, net aggregate
Packet performance	More than 1 million packets per second (line rate)
Latency	0.5-3 ms one-way, typical (depending on air frame period)

## RADIO TECHNOLOGY

Modulation	Cyclic single carrier
Modulation schemes	Ten modulation/coding schemes from QPSK to QAM256, as well as QAM1024
Frequency bands	4.9-6.0 GHz 6.0-6.425 GHz Other frequency bands will be supported in future releases
Channel widths	10, 20 and 40 MHz
Spectral efficiency	Up to 13 bps/Hz
Output power	Up to 27 dBm (average, per Tx chain) @ QPSK to QAM256 Up to 24 dBm @ QAM1024
Receiver sensitivity	-94 dBm @ 10 MHz, QPSK
System gain	Up to 177 dB (based on a 28 dBi integrated antenna in 10 MHz channel width)
Duplex Scheme	TDD, Hybrid-FDD
Antenna	- Integrated: dual-polarization flat panel 23 to 28 dBi (selectable at time of ordering and model-dependent) - Connectorized: 2x N-type (Female) connectors for external dual-polarization antenna
Maximal range	In excess of 100 km in clear line-of-sight conditions, with use of high gain external antennas

## AIR PROTOCOL

Air frame	Configurable, 1 to 10 ms
Uplink/downlink ratio	Configurable, from 50:50 to 99:1 in any direction
Automatic modulation control	Fully supported
Automatic ranging	Fully supported
TDD synchronization	Fully supported, via built-in GLONASS/GPS receiver or IEEE1588 PTP

## WIRED INTERFACES

Ethernet	2x 10/100/1000-BaseT copper ports, RJ-45: GE0 – Data+PoE input GE1 – Data only SFP port: various 3rd party single and multi-mode fibre module sare supported Either of the ports can be configured independently for management, user data or for a hybrid mode
PoE	802.3at or InfiNet-proprietary “passive” PoE
Cable length	Copper Ethernet cable length: up to 100 m between outdoor unit and the primary network connection Fibre cable length: up to 300 m or more depending on the SFP module type

## QOS AND NETWORK PROTOCOLS

QoS	4 queues
Prioritization	“Strict” and “weighted” modes
Packet classification	802.1p, IP ToS, DiffServ, custom L2/L3-based rules
Network protocols	VLAN, IGMP, STP
Timing Transport	IEEE 1588 v2, L2/L4 datagrams, transparent clock

## MANAGEMENT AND INSTALLATION

LED Indication	Power status, wireless and wired link status, RSSI indication, TDD sync status
Management Protocols	HTTP, telnet, SNMP v1/2/3 (MIB-II and proprietary MIBs)
Installation Tools	Antenna alignment tool

## PHYSICAL

Weight and dimensions	Please refer to the model matrix
Operating temperature range	-40° to +60°C
Dust and water protection	IP66
Wind load	160 kph, operational 200 kph, survival
Power supply	IDU-BS-G: 90-240 VAC, 50/60 Hz, 0°C to +40°C, 124x72x38 mm, 0.3 kg
Input DC range	±43 to ±56 VDC
Consumption	Up to a maximum of 30 W

## ACCESSORIES


Spare mounting brackets	MONT-KIT-85 or MONT-KIT-85S
DC injector	AUX-ODU-INJ-G (indoor/outdoor installation)
External lightning protection	AUX-ODU-LPU-G

## COMPLIANCE


Safety	EN 60950-1:2006
Radio	EN 301 893, v.1.7.1 EN 302 502, v.1.2.1 FCC part 15.247 EN 302 328-2
EMC	ETSI EN 301 489-1 ETSI EN 301 489-17 FCC Part 15 Class B
RoHS	Directive 2002/95/EC

## MODEL RANGE

### Integrated Antenna Models

PART NUMBER	FREQUENCY BAND	INTEGRATED ANTENNA	WEIGHT AND SIZE	
Xm/5X.500.2x500.2x23	4900-6000 MHz	Flat-panel, 23 dBi, 10x10 deg	371x371x83 mm 3.1 kg	
Xm/6X.500.2x500.2x24	6000-6425 MHz	Flat-panel, 24 dBi, 8.5x8.5 deg	305x305x66 mm 2.2 kg	
Xm/5X.500.2x500.2x28	4900-6000 MHz	Flat-panel, 28 dBi, 5x5 deg	600x600x75 mm 6.2 kg	
Xm/6X.500.2x500.2x27	6000-6425 MHz	Flat-panel, 27 dBi, 5x5 deg		

### External Antenna Models

PART NUMBER	FREQUENCY BAND	ANTENNA CONNECTION	WEIGHT AND SIZE	
Um/5X.500.2x500	4900-6000 MHz	2xN-type (Female)	253x240x86 mm 2.1 kg	
Um/6X.500.2x500	6000-6425 MHz			

